

MODEL	GROSS CAPACITY		TANK DIMENSIONS		TANK PAD PREPARATION			
	Note: Allowance must be made for air gap and pipework positioning to establish usable tank volume.				Tank Pad Size Required (Diameter x Depth)	Min. Clean Sand Required	Aggregate Required	Water Required After Build
	Litres	Gallons	Diameter	Height				
GT 500	500,659	110,129	14.04m	3.24m	16.04m x 150mm	30.30 m <sup>3</sup>	0.83m <sup>3</sup>	46,429L
GT 410	409,836	90,151	12.70m	3.24m	14.70m x 150mm	25.46 m <sup>3</sup>	0.75m <sup>3</sup>	38,006L
GT 370	367,831	80,911	12.03m	3.24m	14.03m x 150mm	23.20 m <sup>3</sup>	0.71 m <sup>3</sup>	34,111L
GT 330	328,096	72,171	11.36m	3.24m	13.36m x 150mm	21.04 m <sup>3</sup>	0.67 m <sup>3</sup>	30,426L
GT 290	290,632	63,930	10.70m	3.24m	12.70m x 150mm	18.99 m <sup>3</sup>	0.63 m <sup>3</sup>	26,952L
GT 280	276,180	60,751	12.70m	2.18m	14.70m x 150mm	25.46 m <sup>3</sup>	0.75 m <sup>3</sup>	38,006L
GT 250	247,874	54,525	12.03m	2.18m	14.03m x 150mm	23.20 m <sup>3</sup>	0.71 m <sup>3</sup>	34,111L
GT 220	221,097	48,635	11.36m	2.18m	13.36m x 150mm	21.04 m <sup>3</sup>	0.67 m <sup>3</sup>	30,426L
GT 200	195,851	43,081	10.70m	2.18m	12.70m x 150mm	18.99 m <sup>3</sup>	0.63 m <sup>3</sup>	26,952L
GT 170	172,134	37,864	10.03m	2.18m	12.03m x 150mm	17.04 m <sup>3</sup>	0.59 m <sup>3</sup>	23,688L
GT 150	149,948	32,984	9.36m	2.18m	11.36m x 150mm	15.20 m <sup>3</sup>	0.55 m <sup>3</sup>	20,635L
GT 130	129,292	28,440	8.69m	2.18m	10.69m x 150mm	13.46 m <sup>3</sup>	0.51 m <sup>3</sup>	17,792L
GT 110	110,166	24,233	8.02m	2.18m	10.02m x 150mm	11.83 m <sup>3</sup>	0.47 m <sup>3</sup>	15,160L
GT 90	92,570	20,363	7.35m	2.18m	9.35m x 150mm	10.31m <sup>3</sup>	0.43 m <sup>3</sup>	12,739L
GT 80	76,504	16,829	6.68m	2.18m	8.68m x 150mm	8.89 m <sup>3</sup>	0.39 m <sup>3</sup>	10,528L
GT 60	61,968	13,631	6.02m	2.18m	8.02m x 150mm	7.57 m <sup>3</sup>	0.35 m <sup>3</sup>	8,528L
GT 50	48,963	10,770	5.35m	2.18m	7.35m x 150mm	6.36 m <sup>3</sup>	0.32 m <sup>3</sup>	6,738L
GT 40	37,487	8,246	4.68m	2.18m	6.68m x 150mm	5.26 m <sup>3</sup>	0.28 m <sup>3</sup>	5,159L
GT 30	27,542	6,058	4.01m	2.18m	6.01m x 150mm	4.26 m <sup>3</sup>	0.24 m <sup>3</sup>	3,790L
GT 20	19,126	4,207	3.34m	2.18m	5.34m x 150mm	3.36 m <sup>3</sup>	0.20 m <sup>3</sup>	2,632L
GT 10	12,241	2,693	2.67m	2.18m	4.67m x 150mm	2.57 m <sup>3</sup>	0.16 m <sup>3</sup>	1,684L
Warranty - Model size GT 10 – GT 280 (20 year conditional structural warranty and 20 year conditional warranty against leakage). Model size GT 290 – GT 500 (10 year conditional structural warranty and 10 year conditional warranty against leakage).								